



Size, economy, efficiency, integrity...all add up to Zzz-PAP, a breakthrough system that redefines comfort and quality

MINI CPAP UNIT

The Probasics Zzz-PAP™ by PMI delivers performance, simplicity, style, and value in a very small package. The Zzz-PAP offers easy patient setup with a 4-20 cmH₂O pressure range, a comfortable 0-45 minute ramp feature and manual altitude adjustment. PMI also offers the optional Probasics Zzz-PAP Heated Humidifier that quickly and easily integrates to the Zzz-PAP unit providing excellent relief from the symptoms of dryness and congestion associated with CPAP therapy. Weighing less than two pounds and coming standard with an auto-adjusting 100 Volt/240 Volt Universal Power Supply, the compact Zzz-PAP is not only an excellent choice for your bedside but it's perfect for travel as well. Best of all, the Probasics Zzz-PAP is backed by a two-year manufacturer's warranty which we all know is the most necessary feature for providing both the patient and the dealer with peace of mind.



INTEGRATED HEATED HUMIDIFIER

PMI offers an Integrated Heated Humidifier system designed for use with the Probasics Zzz-PAP™ and Zzz-PAP AUTO units. It relieves nasal irritation and dryness which result from constant airflow by supplying the required humidity to the upper airway. With a reliable and safe design featuring overheat protection and a water chamber safety switch, the Probasics Zzz-PAP Integrated Heated Humidifier can drastically improve the patient's comfort level and compliance



The Zzz-PAP™ and Zzz-PAP AUTO units mount directly on the Integrated Heated Humidifier

Zzz-PAP AUTO™

Simply outstanding!
...the ultimate in simplicity, functionality and value.

AUTO CPAP UNIT

Much like the the Probasics Zzz-PAP™, the Probasics Zzz-PAP™ AUTO delivers performance, simplicity and value in a very small package. The difference is the Zzz-PAP™ AUTO also offers an Auto CPAP mode with automatic altitude adjustment as well as compliance and efficacy monitoring with download to a Mini-SD Card. The Zzz-PAP™ AUTO's flow sensing technology utilizes a special honeycomb structure to create a constant flow resistance for minimizing pressure swing. The net result is a quiet, smooth and effective unit that provides effective Auto-CPAP therapy. The Probasics Zzz-PAP™ AUTO also offers features such as automatic shut-off and a clock with a functional alarm. Each unit comes standard with a mini SD card with SD adaptor (USB-SD card reader sold separately), USB cord, and Zzz-Ware Compliance and Efficacy Software.



Mini SD Card & SD Adaptor USB-SD Card Reader

Zzz-WARE Compliance & Efficacy Software: Captures, Displays, Graphs and Prints Total Operating Time of the Unit, Compliance Data and Event Data (AI, HI, SI).

ORDERING INFORMATION

- 7520 Zzz-PAP Core Package**
(Unit Complete with Heated Humidifier)
- 7521 Zzz-PAP Unit Only**
- 7620 Integrated Heated Humidifier only**
- 7601 Replacement Humidifier Chamber**
- 7510 Replacement Filters (Pack of 10)**

- 7540 Zzz-PAP AUTO Core Package**
(Unit Complete with Heated Humidifier)
- 7541 Zzz-PAP AUTO (Unit only)**
- 7545 USB - SD Card Reader**

Note: All Zzz-PAP and Zzz-PAP AUTO units come complete with Operator's Manual, Carrying Bag, 6' Tube and AC Power Cord.

SPECIFICATIONS

Zzz-PAP™

C-PAP and Auto C-PAP Units

	Zzz-PAP	Zzz-PAP AUTO
Pressure Range	4.0 - 20.0 cmH ₂ O (0.5 cmH ₂ O increment)	4.0 - 20.0 cmH ₂ O (0.5 cmH ₂ O increment)
Ramp Time	0 - 45 min (5 minute increments)	0 - 45 min (5 minute increments)
Altitude Compensation	Manual Adjustment	Auto Adjustment
Leak Compensation	N/A	Yes
Compliance Monitoring	N/A	Yes
Events Detection (AI/HI/SI)	N/A	Yes
Download Capacity	N/A	Yes
Clock w/Alarm Function	N/A	Yes
Device Operating Meter	9999.9 hr	9999.9 hr
Heated Humidifier	Optional	Optional
Sound Level	30 dBA @ 10 cmH ₂ O	30 dBA @ 10 cmH ₂ O
Dimension (W x D x H)	5.8"x5"x3.9"	5.8"x5"x3.9"
Weight	1.77 lbs.	1.77 lbs.
Power Supply	100V-240V, 50/60Hz, Universal Power Supply	100V-240V, 50/60Hz, Universal Power Supply
Operating Temperature	41°F to 95°F	41°F to 95°F
Environment Humidity	15% to 95% RH	15% to 95% RH
Warranty	Two years	Two years

Zzz-PAP™

Integrated Heated Humidifier

- Integrates with Probasics **Zzz-PAP** and **Zzz-PAP AUTO** units
- Easy to use rotary knob for heating level adjustment
- Dishwasher safe water chamber has an easy to remove base plate for cleaning
- Safe & reliable with overheat protection and water chamber safety switch
- Indicators clearly show when **Power is ON** and **Heater is ON**

Power Supply	100V-240V, 50/60Hz (Universal)
Water Capacity	450 ml
Heater Settings	1 - 6 (Heater plate temperature 86°F to 140°F)
Warm-Up Time	< 30 minutes
Pressure Drop	0.2 cmH ₂ O @ 60LPM
Humidity Output	10 - 40 mgH ₂ O/L
Indicator	Power On indicator, Heater On indicator
Dimension (W x D x H)	Heater: 6.8" x 10" x 1.6" Water Chamber: 4.5" x 5.9" x 4.2"
Weight	Heater: 0.84 lb Water Chamber: 0.53 lb
Warranty	One year

PROBASICS™
by PMI

Probasics™

15 South Main Street

Second Floor, Unit F

Marlboro, NJ 07746

Tel. 800.438.0503

Fax 732.683.1945

www.pmiusa.biz

All specifications are subject to change without notice.

Economies of scale

Zzz-PAP AUTO™

Zzz-PAP™

PROBASICS™
by PMI

